



Sma 10kw 3 phase inverter

The Sunny Tripower X is the latest in commercial solar energy generation and the new centerpiece of the proven SMA Energy System Business. As a comprehensive solution, the integrated System Manager enables complete energy management from one platform while combining state-of-the-art technology into one device. This design ensures small- to medium-sized businesses can accommodate all energy management and needs, today and in the future.

The MD.SEN-US-40 is compatible with the Sunny Tripower X 20-US / 25-US / 30-US with hardware version A2 or newer. The hardware version can be found on the packaging label of the SMA Sensor Module.

The S0 interface of the SMA Sensor Module cannot be used for the Sunny Tripower X. It is therefore not possible to operate an anemometer or energy meter with the Sunny Tripower X by connecting them to the S0 interface of the SMA Sensor Module.

In connection with an energy meter, an SMA System Manager takes over closed-loop control at the point of interconnection and can control or regulate subordinate inverters. The System Manager also takes over system monitoring and communication to the Sunny Portal powered by ennexOS.

The Sunny Home Manager can be used as a superordinate device but is not able to fully perform the functions of the System Manager. For example, the Sunny Home Manager cannot be used for reactive power control.

From firmware version 03.02.07.R the transmission protocol of Sunny Tripower X has changed from http to the secure transmission protocol https. The user interface of the Sunny Tripower X is accessible via https://SMA[serial number] or https://SMA[serial number].local from firmware version 03.02.07.R.

Sma 10kw 3 phase inverter



Web: https://www.sumthingtasty.co.za/contact-us/ Email: energystorage2000@gmail.com WhatsApp: 8613816583346

